

Touch Screen Kiosk

TECHNICAL SPECIFICATIONS

General	Screen size	15"	22"	32"
	Panel type	LED-backlit TFT LCD	LED-backlit TFT LCD	LED-backlit TFT LCD
	Brightness	270 cd/m2	225 cd/m2	400 cd/m2
	Aspect ratio	16:9	16:9	16:9
	Resolution	1366 x 768	1920 x 1080 px	1920 x 1080 px
	Viewing angle	160° horizontal / 160° vertical	170° horizontal / 160° vertical	178° horizontal / 178° vertical
	Signal input	DP / VGA / HDMI	DP / VGA / HDMI	DP / VGA / HDMI
	Control	OSD	OSD	OSD
	Life cycle	50'000 hours	50'000 hours	50'000 hours
	Operation length	24h/day	24h/day	18h/day
	Screen orientation	landscape	landscape	landscape
	Warranty	3 years	3 years	3 years
	Packaging	wooden box / foam plastic	wooden box / foam plastic	wooden box / foam plastic
Environment	Environment rating	Indoor IP51	Indoor IP51	Indoor IP51
	Operating temperature	0°C / +40°C	0°C / +40°C	0°C / +40°C
	Environment humidity	20% - 80%	20% - 80%	10% - 90%
Enclosure	Main material	high quality welded steel enclosure	high quality welded steel enclosure	high quality welded steel enclosure
	Finish	powder coated RAL colours	powder coated RAL colours	powder coated RAL colours
	Maintenance access	rear side opening	rear side opening	rear side opening
	Mounting	freestanding	freestanding	freestanding
	Hardware protection	active cooling / dust protection system	active cooling / dust protection system	active cooling / dust protection system
Power	Power consumption	17W	20W	42W
	Power supply	AC 230 V, 50/60 Hz	AC 230 V, 50/60 Hz	AC 100-240 V, 50/60 Hz
Optional	Touch sensor	capacitive 10 touch	capacitive 10 touch	capacitive 40 touch
	PC	Intel NUC / A-Open etc.	Intel NUC / A-Open etc.	Intel NUC / A-Open etc.
	Branding	sticker	sticker	sticker
Kiosk dimensions	Height	113 cm	122 cm	122 cm
	Floor plate to display	99 cm	106 cm	100 cm
	Width	44 cm	57 cm	80 cm
	Depth	40 cm	35 cm	60 cm
	Weight	55 kg	64 kg	76 kg
Poster dimensions	Poster height	991.0 mm	976.0 mm	973.0 mm
	Poster width	438.5 mm	563.0 mm	792.0 mm

